


# VPR11/15

# VANDALITES - ROUND



### DIMENSIONS

### VPR11 & VPR15 HID



Fixture	Width (A)	Height (B)	Ballast Housing Depth (C)
VPR11	11-3/8" (287mm)	4-3/4" (121mm)	3-1/2" (89mm)
VPR15	15-1/8" (385mm)	5-1/8" (131mm)	3-1/2" (89mm)



**APPLICATION** - Constructed of durable polycarbonate, and suitable for indoor or outdoor use. Available in an eleven or fifteen inch diameter with multiple lamp and wattage choices. The vandal resistant polycarbonate lens with internal prisms provides a symmetrical distribution. The smooth exterior is unobtrusive and easy to keep clean.

**HOUSING** - Blanked and die formed from 16 ga crs with white polyester powder coated finish.

**SHIELDING** - Clear polycarbonate prismatic diffuser secured with molded lugs and spanner head tamper proof screws.

**BALLAST - HID** - Magnetic core and coil type, specify 120V or 277V.

**BALLAST HOUSING - HID** - Spun .060 aluminum with (4) 7/8" diameter knock outs on outside surface, (2) knock outs on back. White polyester powder coated finish.

**SOCKET - HID** - Medium or mogul base pulse rated for 4kv.

**LAMPS** - Metal halide and high pressure sodium, (by others).

**PHOTOMETRICS** - Please visit our web site at [www.lsi-industries.com](http://www.lsi-industries.com) for detailed photometric data.

**LISTING** - UL Listed to U.S. and Canadian safety standards. Suitable for wet location. IBEW Union made.

**FASTENERS** - Spanner head tamper-proof screws are shipped standard. Other head types available (see options).

## LUMINAIRE ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: **LIVPR11 1 50MH F UE**

Prefix	Lamps	Lamp Type	Options	Voltage
LIVPR11 (Small)	2	50MH - 50W MH 70MH - 70W MH 70HPS - 70W HPS	CH - Clutch Head CPA - Center Pin Allen Head TORX - Torx Head F - Fusing EM - Emergency Pack <sup>1</sup> PC - Photo Control SC - Surface Collar (required on HID unit)	UE - Universal Electronic (120-277V) 120 - 120V 277 - 277V 347 - 347V
LIVPR15 (Large)	1	50MH - 50W MH 70MH - 70W MH 70HPS - 70W HPS 100HPS - 100W HPS 150HPS - 150 W HPS		

1 - Must be ordered w/ surface collar